



HIKVISION
intrusion

Wired volumetric double technology detector

KX15DTAM

DETECTION

Detector type	Wired
Installation height	1.8 m ~ 2.4 m
Angle detection	85°
Detection distance	15 m
Detection method	Infrared and microwave
Coverage	15 m / 85°
Antimasking	Yes
Adjustable antimasking	Sí
Blue Wave technology (infrared noise improvement)	Sí
Anti-cloaking technology (activation of alarm after infrared detection AND / OR microwave)	Sí
PIR detection advance at ground level (PIR Creep)	Sí
IFT technology	Sí
Detection technology	Volumetric double technology

CERTIFICATION

Grade	3
Normative	EN50131
Environmental class	II

POWER CONSUMPTION

Power mode	DC
Voltage	9V ~ 16V

MATERIAL AND DIMENSIONS

Dimensions	114 x 67 x 47 mm
Material	Plastic

SENSOR

Type of sensor	Pyro-electric
Automatic sensitivity	Sí
Curtain sensor	Sí
Microwave	3 microwave frequencies to avoid interference.

TECHNICAL SPECIFICATIONS

LED indicators	Yes
Tamper	Yes
EOL resistors (end of line)	Sí

AMBIENT

Operating temperature	-30 °C ~ 70 °C
Use	Indoor

LENS

Interchangeable lenses	Sí
------------------------	-----------

