

HIKVISION
HiWatch Series



Bullet ip camera of 4 megapixels and fix lens

HWI-B140H-M

VIDEO (CAMERAS)

Video Resolution	4 Megapixels
BLC	Yes
3D-NR	Yes
AGC	Yes
WDR	WDR (120 dB)
Images per second	20fps
Video output	RJ45
Day / night mode	Automatic / Manual
Privacy mask	Yes
Bit rate	32Kbps ~ 8Mbps
Compression	H.265+ / H.265 / H.264
Main stream	4Mpx (1 ~ 20fps) / 3Mpx / 1080P / 720P (1 ~ 25fps)
Sub stream	640 × 480 / 640 × 360 / 320 × 240 (25fps)
Watermark	Yes
Anti flap	Yes
Mirror	On / Off

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	5W
Amperage	400mA
PoE power	Yes
Type PoE	PoE 802.3af

AMBIENT

Operating temperature	-30 °C ~ 50 °C
Degree of protection	IP67
Use	Indoor-outdoor
Maximum humidity	95%

LENS

Lens Type	Fix
Focal distance	2.8 mm

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, type S y G
Maximum number of users	Up to 32 users
Web browser	Explorer / Chrome / Firefox / Safari
Management software	iVMS-4200 / iVMS-5200 / Hik-Connect
Mobile devices	Android / IOS (Apple)
Live view	Up to 6 channels
IP address filter	Yes

IMAGE

Sensor	CMOS ®
Sensor resolution	2560 x 1440
Sensor Size	1/1.3'
Electronic shutter speed	1/3 ~ 1/100000s
Minimum lighting	0.1Lux

MATERIAL AND DIMENSIONS

Dimensions	191.3 x 70 (Ø) mm
Material	Metal
Net weight	400 g
Weight with packaging	640 g

DISTANCE DORI

Detect	56 m
Observe	23 m
Recognize	11 m
Identify	5 m

VIDEO ANALYSIS

Detection type	Basic motion detection (pixel difference)
Motion detection	Yes
Video Tamper	Yes

AXES

Motion	3-Axis
--------	---------------

technical datasheet

Maximum diaphragm opening	F/2.0
Angle of View	100°

NIGHT VISION

Night vision distance	30 m
Type of night vision	IR
Wavelength	850 nm

GENERAL INFORMATION

Technology	IP
Type of camera	Bullet

STORAGE

Storage Systems

NAS

